



HRL series HRL 1280W



Valve Regulated Lead Acid Battery

Maintenance-Free Sealed Lead Acid Battery.
Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99%.

General Design for Standby Power Applications

【Design Life】

Up to 8 Years in Standby Service at 25°C
Eurobat (20°C) : 10/12 YEARS LONG LIFE

【Operating Temperature Range】

Nominal Operating Temperature : 25°C (77°F)
Discharge : -15°C ~ 50°C (5°F~122°F)
Charge: -15°C ~ 40°C (5°F~104°F)
Storage: -15°C ~ 40°C (5°F~104°F)

【Float Charging Voltage】

13.5 ~ 13.8 VDC/Unit at 25°C (77°F)

【Equalization Charging Voltage】


14.4 ~ 15.0 VDC/Unit at 25°C (77°F)

【Self Discharge】

Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F);
Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F).

Specification Design according with IEC 61056-1/2:2012

Nominal Voltage	12V (6 cells per unit)		
Nominal Capacity	80W @15min-rate to 1.67V per cell @25°C (77°F)		
Weight	Approx. 6.60 Kg (14.55 lbs)		
Maximum Discharge Current	300A (5sec)		
Internal Resistance	Approx. 9.00 mΩ		
Short Circuit Current	723A		
Maximum Charge Current	8.0A		
Terminal types	I1 thread lead alloy terminal to accept M5 bolt		
Terminal tightening torque	30.4±6.1 Kgf·cm / 26.4±5.3 Lbf·in / 3.0±0.6 N·m		
Container Material	ABS (UL 94-HB) & Flame Retardant (94-V0) available upon request		
Dimensions	Length (L)	181.0±2.0 mm	7.13±0.08 inch
	Width (W)	76.0±1.0 mm	2.99±0.04 inch
	Container Height (h)	165.0±2.0 mm	6.50±0.08 inch
	Overall Height (H)	165.0±2.0 mm	6.50±0.08 inch



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

F.V/Time	2MIN	4MIN	5MIN	6MIN	8MIN	10MIN	15MIN	20MIN	30MIN	45MIN	60MIN	90MIN
1.60V	165	113	98.4	87.9	72.3	62.4	44.4	35.0	24.9	18.2	14.6	10.6
1.67V	142	103	90.7	81.7	69.5	58.7	43.5	34.0	24.6	18.0	14.4	10.4
1.70V	133	98.6	88.3	80.7	67.8	58.1	42.4	33.7	24.3	17.7	14.2	10.2
1.75V	119	92.3	82.6	75.5	64.3	54.3	41.6	32.9	23.7	17.4	14.0	10.1
1.80V	105	83.2	75.7	70.0	60.8	51.8	39.8	32.1	23.0	16.9	13.6	10.0
1.85V	92.3	76.6	70.1	65.2	56.8	49.2	37.6	30.1	22.1	16.6	13.5	9.84

Constant Power Discharge Characteristics Unit: W (25°C, 77°F)

F.V/Time	2MIN	4MIN	5MIN	6MIN	8MIN	10MIN	15MIN	20MIN	30MIN	45MIN	60MIN	90MIN
1.60V	1584	1171	1047	955	790	691	496	391	282	209	169	122
1.67V	1431	1073	971	895	761	661	485	382	280	207	167	121
1.70V	1369	1045	953	884	743	660	475	381	275	204	165	118
1.75V	1270	983	897	832	708	626	468	370	270	200	161	117
1.80V	1173	909	836	781	679	593	453	364	266	197	159	116
1.85V	1091	855	786	734	641	561	426	346	257	192	156	115

Please refer to the official site for the latest rating confirmation. URL: www.csb-battery.com

Issued: 200930

Sales Offices

希世比能源科技股份有限公司
CSB Energy Technology Co., Ltd.

BUSINESS HEADQUARTERS

Tel: +886-2-2880-5600
Fax: +886-2-2888-3300

USA OFFICE

Tel: +1-817-244-7777 / 1-(800)3-CSB-USA (272872)
Fax: +1-817-244-4445

SHENZHEN OFFICE (CHINA)

Tel: +86-755-8831-6488/6775/6075
Fax: +86-755-8831-6548

EUROPE (EMEA) OFFICE

Tel: +31(0)180-418-140
Fax: +31(0)180-418-327

SHANGHAI OFFICE (CHINA)

Tel: +86-21-5046-1622/0833/0094
Fax: +86-21-5046-1046

Recognized under UL 1989,
and certified by ISO 9001, 14001, 45001, 50001.



TAIPEI OFFICE

Tel: +886-2-2880-5600
Fax: +866-2-2888-3300

BEIJING OFFICE (CHINA)

Tel: +86-10-6597-8065/8165/8265
Fax: +86-10-6597-8565